

Narada lithium storage

With technology of LFP cells

energy@tempelgroup.com

+34 93 600 36 00



High voltage solution

Narada lithium cell

Brief introduction



Narada NLC series of lithium-ion cell

Narada NLC series cell are made by LFP (LiFePO₄) and NMC (LiNiMnCoO₂) technologies, available in both pouch and prismatic forms with light weight, stable performance and high energy density





Narada lithium cell


Dimension of prismatic cell



Narada lithium cell

Specification of NLC cell

Model	NLC36130255PF	
Rated voltage	3.2V	
Rated capacity	80Ah	
Discharge current	240A (Continuous)	
Charge current	80A (Standard)	
Discharge current	80A (Standard)	
Charge current	160A (Maximum)	
Charge voltage	3.65V (Limit)	
Cut-off voltage	2.5V	
Impedance	≤ 1.0mΩ	
Length of cell	130.0mm	
Width of cell	37.0mm	
Height of cell	243.0mm	





NESP lithium module

Dimension of module



NESP housing






Narada NLC cell






NESP module









NESP lithium module

Specification of module

Model	19NESP160	38NESP80
Rated voltage	19.2V	38.4V
Rated capacity	160Ah	80Ah
Cell connection	6*2strings	12*1string
Dimension	510.0*181.6*264.4mm	
Weight	35kg	
Temperature range	Discharge: -20 to +60°C Charge: 0 to +60°C Storage: 0 to +40°C	
Recommended temperature	Discharge: +15 to +35°C Charge: +15 to +35°C Storage: +15 to +30°C	
Humidity	5% to 95%	



Modules connection in system



System introduction





Whole integrated storage system with both lithium modules and BMS, quite convenient in both maintenance and installation, extendable to large scale

- Customized system with flexibility
- Wide range of voltage and capacity
- Modular design for easy installation
- Integrated with battery management




Function and diagram of BMS

Principal function

- System protection:
 - Over or under temperature & voltage
- Short circuit or communication failure
- Over current of charge or discharge
- Data acquisition:
 - Cell voltage and temperature
 - Cumulative charge/ discharge power
 - Current & capacity of battery module
- Cell balancing
- SOC & communication


Optional function

- LCD display interface
- EEROM for data storage
- Current limit setup: 2A~25A






System configuration



Stored Energy Solutions for a Demanding World!

Commercial system composition



Stored Energy Solutions for a Demanding World!





Low voltage solution

General introduction








Narada 48NPFC series

Made of LiFePO4 (lithium iron phosphate) cells with 48V integrated with smart BMS for remote monitoring as well as maintenance, suitable for many applications of energy storage


- No active cooling units required
- Compact, space saving for cabinet
- Easier site planning and installation
- More safety and operational reliability
- High efficiency and longer service life



System composition



Schematic diagram



- LFP cell: Chemical power source, for energy storage and power supply
- Monitoring: Optional component according to requirement from clients
- Ch. & disch. management: Current limit for charge & discharge circuit
- Cell protection: Against short-circuit, over-charge, over-current...etc.
- Cell balancing: System equalization to those unbalanced LFP cell



Interface of front panel







Module 48NPFC80



Specification	Value
Rated capacity (at 25 ℃)	80Ah(C ₅)
Recommended charge current	16A
Max. charge/discharge current	80A
Charge voltage/End voltage	54±0.5V/40.5V
Weight	44kg










Module 48NPFC100



Specification	Value
Rated capacity (at 25 ℃)	100Ah(C ₅)
Recommended charge current	20A
Max. charge/discharge current	100A
Charge voltage/End voltage	54±0.5V/40.5V
Weight	45kg









Separated storage cabinet



A completed storage solution, consists of NPFC modules, monitoring platform, connection box, as well as EMS, ideally for general requirement



- Automatic operational mode
- Smart App for remote monitoring
- Optimize profit of PV system



- Modular design for flexible setup
- Plug & Play for easier installation
- **Compatible** with most of inverters



- **5 years** product warranty
- 7 years performance warranty
- 15 years expected service life



Composition of cabinet

Solar inverter

Compatible with most type of both battery inverter and hybrid inverter

EMS & connection


Real-time system regulation for energy balance and economics

Battery modules

Installed with two modules of 48NPFC80 lithium-ion batteries

Monitoring

Remote data monitoring for both laptop and mobile telecom devices






Cabinet specification

Parameters	Description		
Innut	Rated input AC voltage	220-240V@1-Phase or 400V@3-Phase	
Input	AC frequency	50 Hz/60 Hz	
(AC-Utility grid)	Max. line current	60 A	
Topus	Rated input AC voltage	220-240V@1-Phase or 400V@3-Phase	
Input	AC frequency	50 Hz/60 Hz	
(AC-PV interface)	Max. line current	60 A	
Output	Rated output AC voltage	220-240V@1-Phase or 400V@3-Phase	
Output	AC frequency	50 Hz/60 Hz	
(AC-normal load)	Max. line current	60 A	
Output	Rated output AC voltage	220V/230V/240V@1-Phase	
Output	AC frequency	50 Hz/60 Hz	
(AC-UPS load)	Continuous power@25°C	3500 VA	
	Power 30 min. / 5 sec. @25°C	4000 VA / 10.5 kVA	
	Power factor	0.1~1	



Residential system composition



Monitoring system









Functions of monitoring

- Data generation, storage, consumption
- Warning & analysis for system failure
- Both real-time and historical records
- Flexible demonstration by any time
- Available for both IOS and Android



Integrated storage cabinet



An integrated system, consists with Narada NPFC modules, inverter, monitoring platform, EMS and connection box, ideally for high-end requirement



- Automatic operational mode
- One-stop integrated solution
- Smart energy management



- Modular design for maintenance
- Plug & Play for easier installation
- Available for many other inverters




- **5 years** product warranty
- 7 years performance warranty
- 15 years expected service life



Stored Energy Solutions for a Demanding World!

Composition of cabinet





Cabinet specification

Parameter	3KW/11.5KWh	6KW/11.5KWh
Dimensions (W*D*H)	600*700*1600mm	
System weight	<280 Kg	<300 Kg
Nominal/Available capacity	11.5KWh / 9.21KWh (@ 80% DOD)	
Operating voltage range	48V (@[40,100])	
Maximum charging power	3.0KW	6.0KW
Maximum charging current	60A / 45A	120A / 90A
Charge/Discharge efficiency	93.5%	
Grid feed-in	3N ~ 400V	
Inverter certification	VDE-AR-N4105 / IEC62109 / VDE0126 / CE	
Battery configuration	3pcs of 48V80Ah modules in parallel	
Battery lifespan	>5000 times (@ 80% DOD)	
Battery certification	CE / UN 38.3	
Energy management system	9 inch touch screen with full color	
Communication access	RS485 / RS232 / USB / Ethernet / WiFi	



Operational modes

Under normal grid condition



Daytime:

Loads firstly get PV energy, whose rest will be stored in cabinet, and residue into grid

At night:

Loads firstly get energy from battery, then from grid if storage capacity is not enough

Under abnormal grid condition



On-grid to off-grid:

System will automatically switch to off-grid mode for vital loads when grid is abnormal

Off-grid to on-grid:

System will switch back automatically from off-grid to on-grid mode when grid normal





Stored Energy Solutions for a Demanding World!

Specialty of integrated cabinet





- System Highlights
- Compact and one-stop integration
- Smart management for more profit
- Auto-switch for on & off grid mode
- Long lifespan with >7years warranty
- Touchable screen for local monitoring

More options of appearance available



More cabinet reference











Projects of power storage

Energy storage project for Grid India

Katwaria Sarai, New Delhi, India





Project inginights

The first oversea project of energy storage, which consists of both Narada lead-carbon battery and lithium battery



- Storage capacity: 1MWh
- Pb-C batteries: 500KWh
- Li-ion batteries: 500KWh
- Function: Frequency modulation
- Project date: 2016.08




Energy storage project for Grid India

Katwaria Sarai, New Delhi, India













Storage project for premier school

Peshawar, Pakistan





- Storage power: 30KWp
- Storage capacity: 84KWh
- Battery type: NLC36130255PF
- Battery quantity: 324pcs
- Project date: 2016.11



Storage project for premier school

Peshawar, Pakistan











Storage project for grid distribution

Xuzhou city, Jiangsu, China





- Storage power: 300KWp
- Storage capacity: 344KWh
- Battery type: NLC36130255PF
- Battery quantity: 1344pcs
- Project date: **2016.12**




Storage project for grid distribution

Xuzhou city, Jiangsu, China











Residential solution of Narada HESS

Nantong city, Jiangsu, China





- PV generation: 5KWp
- Storage capacity: **7.2KWh**
- Battery type: **48NPFC75**
- Battery quantity: 2pcs
- Project date: **2014.10**



Residential solution of Narada HESS

Gu An city, Hebei, China



Project Details

- PV generation: 10KWp
- Storage capacity: **57.6KWh**
- Battery type: 48NPFC75
- Battery quantity: 8pcs
- Project date: **2015.07**



Residential solution of Narada HESS

Gu An city, Hebei, China













Stored Energy Solutions for a Demanding World!

Thanks!